

Product



AGM VRLA Series

BATTERY TYPE	NOMINAL VOLTAGE (V)	NOMINAL CAPACITY (Ah)		DIMENSIONS						HT OVER TERMINAL		WEIGHT (APPROX.)		ASSEMBLY FIGURE	
				L	W	H	L	W	H					TERMINAL POSITION	TERMINAL TYPE
		5HR	20HR	in	in	in	mm	mm	mm	in	mm	lbs	kg		
WP1.2-6	6	1.02	1.2	3.82	0.98	2.05	97	25	52	2.24	57	0.65	0.30	2	F1
WP4-6	6	3.4	4	2.76	1.85	4.00	70	47	101.5	4.17	106	1.64	0.75	1	F1
WP4-6B	6	3.4	4	2.76	1.85	4.00	70	47	101.5	4.17	106	1.64	0.75	1	F1
WP4.5-6	6	3.83	4.5	2.76	1.85	4.00	70	47	101.5	4.17	106	1.80	0.82	1	F1
WP7-6	6	5.95	7	5.94	1.34	3.70	151	34	94	3.94	100	2.64	1.20	2	F1
WP7-6S	6	5.95	7	4.57	1.97	3.62	116	50	92	3.90	99	3.19	1.45	1	F1
WP9-6A	6	7.65	9	3.88	2.20	4.65	98.5	56	118	4.65	118	3.74	1.70	19	F1
WP10-6	6	8.5	10	5.94	1.97	3.70	151	50	94	3.94	100	3.74	1.70	2	F1
WP12-6S	6	10.2	12	5.94	1.97	3.70	151	50	94	3.90	99	4.05	1.84	2	F1
WP13-6	6	11.1	13	4.25	2.76	5.51	108	70	140	5.51	140	4.93	2.24	17	F1-,F2+
WP20-6	6	17	20	6.18	3.27	4.92	157	83	125	4.92	125	8.80	4.00	20	F3
WP0.7-12	12	0.6	0.7	3.78	0.98	2.44	96	25	62	2.44	62	0.88	0.40	8	Wire/A
WP0.7-12S	12	0.6	0.7	3.78	0.98	2.44	96	25	62	2.44	62	0.88	0.40	8	Wire/J
WP1.2-12	12	1.02	1.2	3.82	1.69	2.09	97	43	53	2.32	59	1.24	0.56	4	F1
WP1.2-12T	12	1.02	1.2	3.82	1.89	1.97	97	48	50	2.20	56	1.30	0.59	4	F1
WP2.2-12	12	1.87	2.2	7.01	1.34	2.36	178	34	60	2.60	66	2.20	1.00	2	F1
WP2.3-12	12	1.96	2.3	7.01	1.34	2.36	178	34	60	2.60	66	2.29	1.04	2	F1
WP2.6-12	12	2.21	2.6	7.01	1.36	2.36	178	34.5	60	2.60	66	2.20	1.00	2	F1
WP2.9-12T	12	2.465	2.9	3.11	2.20	3.90	79	56	99	4.21	107	2.62	1.19	6	F1
WP2.9-12TR	12	2.465	2.9	3.11	2.20	3.90	79	56	99	4.21	107	2.62	1.19	3	F1
WP3-12	12	2.55	3	5.28	2.64	2.34	134	67	59.5	2.58	65.5	2.86	1.30	4	F1
WP4-12	12	3.4	4	3.54	2.76	3.98	90	70	101	4.21	107	3.52	1.60	3	F1
WP4.5-12	12	3.83	4.5	3.54	2.76	3.98	90	70	101	4.21	107	3.56	1.62	3	F1
WP5-12	12	4.25	5	3.54	2.76	3.98	90	70	101	4.21	107	4.18	1.90	3	F1
WP5-12B	12	4.25	5	3.54	2.76	3.98	90	70	101	4.21	107	3.56	1.62	3	F1
WP5-12SHR	12	4.25	5	3.54	2.76	3.98	90	70	101	4.21	107	4.25	1.93	3	F2
WP7.2-12	12	6.12	7.2	5.94	2.56	3.70	151	65	94	4.02	102	5.28	2.40	5	F1
WP7.2-12A	12	6.12	7.2	5.94	2.56	3.70	151	65	94	4.02	102	5.17	2.35	5	F1
WP7.2-12SHR	12	6.12	7.2	5.94	2.56	3.70	151	65	94	4.02	102	5.28	2.40	5	F2
WP7.2-12TSHR	12	6.12	7.2	5.94	2.56	3.70	151	65	94	4.17	106	5.28	2.40	24	F3
WP7.5-12	12	6.375	7.5	5.94	2.56	3.70	151	65	94	4.02	102	5.06	2.30	5	F1

Product



AGM VRLA Series

BATTERY TYPE	NOMINAL VOLTAGE (V)	NOMINAL CAPACITY (Ah)		DIMENSIONS						HT OVER TERMINAL		WEIGHT (APPROX.)		ASSEMBLY FIGURE	
				L	W	H	L	W	H					TERMINAL POSITION	TERMINAL TYPE
		5HR	20HR	in	in	in	mm	mm	mm	in	mm	lbs	kg		
WP12-12	12	10.2	12	5.94	3.86	3.66	151	98	93	3.86	98	9.02	4.10	5	F1
WP12-12A	12	10.2	12	5.94	3.86	3.66	151	98	93	3.86	98	8.25	3.75	5	F1
WP12-12B	12	10.2	12	5.94	3.86	3.66	151	98	93	3.86	98	8.03	3.65	5	F1
WP12-12T	12	10.2	12	5.94	3.86	3.66	151	98	93	4.09	104	8.84	4.02	24	F3
WP15-12	12	12.75	15	7.13	2.99	6.57	181	76	167	6.57	167	10.58	4.81	11	F3
WP17-12I	12	14.45	17	7.13	2.99	6.57	181	76	167	6.57	167	12.32	5.60	11	F3
WP18-12	12	15.3	18	7.13	2.99	6.57	181	76	167	6.57	167	13.86	6.30	21	F3
WP18-12I	12	15.3	18	7.13	2.99	6.57	181	76	167	6.57	167	13.86	6.30	11	F3
WP18-12N	12	15.3	18	7.13	2.99	6.57	181	76	167	6.57	167	13.86	6.30	14	F6
WP18-12NSHR	12	15.3	18	7.13	2.99	6.57	181	76	167	6.57	167	12.32	5.60	14	F6
WP18-12SHR	12	15.3	18	7.13	2.99	6.57	181	76	167	6.57	167	12.32	5.60	11	F3
WP20-12	12	17	20	7.13	2.99	6.57	181	76	167	6.57	167	13.09	5.95	21	F3
WP20-12I	12	17	20	7.13	2.99	6.57	181	76	167	6.57	167	13.09	5.95	11	F3
WP20-12N	12	17	20	7.13	2.99	6.57	181	76	167	6.57	167	13.09	5.95	14	F6
WP20-12U	12	17	20	7.13	2.99	6.57	181	76	167	6.57	167	13.09	5.95	21	F10
WP22-12N	12	18.7	22	7.13	2.99	6.57	181	76	167	6.57	167	15.18	6.90	14	F8
WP24-12	12	20.4	24	6.54	6.89	4.92	166	175	125	4.92	125	17.60	8.00	21	F3
WP24-12N	12	20.4	24	6.54	6.89	4.92	166	175	125	4.92	125	17.60	8.00	14	F6
WP26-12	12	22.1	26	6.54	6.89	4.92	166	175	125	4.92	125	20.5	9.30	21	F3
WP26-12B	12	22.1	26	6.54	6.89	4.92	166	175	125	4.92	125	17.60	8.00	21	F3
WP26-12N	12	22.1	26	6.54	6.89	4.92	166	175	125	4.92	125	20.5	9.30	14	F6
WP26-12NB	12	22.1	26	6.54	6.89	4.92	166	175	125	4.92	125	17.60	8.00	14	F6
WP30-12T	12	25.5	30	6.54	4.94	6.93	166	125.5	176	6.93	176	23.1	10.5	21	F3
WP40-12	12	34	40	7.83	6.54	6.73	199	166	171	6.73	171	29.7	13.5	11	F4
WP40-12N	12	34	40	7.83	6.54	6.73	199	166	171	6.73	171	29.5	13.4	14	F8
WP45-12	12	38.25	45	7.83	6.54	6.73	199	166	171	6.73	171	31.9	14.5	11	F4
WP45-12N	12	38.25	45	7.83	6.54	6.73	199	166	171	6.73	171	31.9	14.5	14	F8
WP50-12	12	42.5	50	7.83	6.54	6.73	199	166	171	6.73	171	31.9	14.5	11	F4
WP50-12N	12	42.5	50	7.83	6.54	6.73	199	166	171	6.73	171	31.9	14.5	14	F8
WP55-12	12	46.75	55	8.90	5.31	8.15	226	135	207	9.02	229	37.4	17.0	10	F15
WP55-12N	12	46.75	55	8.90	5.31	8.15	226	135	207	8.43	214	37.4	17.0	9	F8
WP65-12	12	55.25	65	13.78	6.54	6.85	350	166	174	6.85	174	51.3	23.3	15	F4
WP65-12B	12	55.25	65	13.78	6.54	6.85	350	166	174	6.85	174	47.5	21.6	15	F4

Product



WP65-12N	12	55.25	65	13.78	6.54	6.85	350	166	174	6.85	174	51.3	23.3	14	F8
WP65-12NB	12	55.25	65	13.78	6.54	6.85	350	166	174	6.85	174	47.5	21.6	14	F8
WP65-12R	12	55.25	65	13.78	6.54	6.85	350	166	174	6.85	174	51.3	23.3	10	F4

BATTERY TYPE	NOMINAL VOLTAGE (V)	NOMINAL CAPACITY (Ah)		DIMENSIONS						HT OVER TERMINAL		WEIGHT (APPROX.)		ASSEMBLY FIGURE	
				L	W	H	L	W	H					TERMINAL POSITION	TERMINAL TYPE
		5HR	10HR	in	in	in	mm	mm	mm	in	mm	lbs	kg		
22NF245C	12	42.5	50	8.90	5.31	8.15	226	135	207	9.02	229	37.4	17.0	15	F15
22NF245CN	12	42.5	50	8.90	5.31	8.15	226	135	207	8.43	214	37.4	17.0	14	F8
22NF305C	12	52.7	62	8.90	5.31	8.15	226	135	207	9.02	229	41.1	18.7	15	F15
22NF305CN	12	52.7	62	8.90	5.31	8.15	226	135	207	8.43	214	41.1	18.7	14	F8

BATTERY TYPE	NOMINAL VOLTAGE (V)	NOMINAL CAPACITY (Ah)		DIMENSIONS						HT OVER TERMINAL		WEIGHT (APPROX.)		ASSEMBLY FIGURE	
				L	W	H	L	W	H					TERMINAL POSITION	TERMINAL TYPE
		15min W/cell	AH	in	in	in	mm	mm	mm	in	mm	lbs	kg		
WP1213W	12	13	3.3	5.28	2.64	2.34	134	67	59.5	2.58	65.5	2.86	1.30	4	F2
WP1224W	12	24	6	5.94	2.01	3.70	151	51	94	3.98	101	4.40	2.00	5	F2
WP7-12(28W)	12	28	7	5.94	2.56	3.70	151	65	94	4.02	102	4.84	2.20	5	F1
WP7-12(28W)T	12	28	7	5.94	2.56	3.70	151	65	94	4.17	106	4.82	2.19	24	F3
WP1236W	12	36	9	5.94	2.56	3.70	151	65	94	4.02	102	5.94	2.70	5	F2
WP1236WT	12	36	9	5.94	2.56	3.70	151	65	94	4.17	106	5.94	2.70	24	F3
WP1251W	12	51	12	5.94	3.86	3.66	151	98	93	3.86	98	8.58	3.90	5	F2
WP1251WT	12	51	12	5.94	3.86	3.66	151	98	93	4.09	104	8.58	3.90	24	F3